

**AEC-UPS
Uninterruptible
Power
Supplies**

**AEC Online
Double Conversion
10-20**



armenelectric
www.aec-ups.com



AEC Online Double Conversion 10-20

Specification

Model	10KVA	15KVA	20KVA
Capacity	7KW	10.5KW	14KW
INPUT			
Phase	Single	3 Phase with Ground	
Frequency Range	46~54HZ		
Acceptable Voltage	60~138VAC		
OUTPUT			
Phase	Single		
Voltage	220VAC/230VAC/240VAC		
Voltage Regulation	±1%		
Frequency (Synchronized Range)	46~54Hz		
Frequency (Battery Mode)	50 ± 0.05Hz		
Current Crest Ratio	3:1		
Harmonic Distortion	≤ 2% THD (Linear Load) / ≤ 6% THD (Non-Linear Load)		
Output Waveform	Pure SineWave		
Numbers of Batteries	16		
Charging Current (Max.)	4.2A		
Charging Voltage	274VDC ±1%V		
DIMENSION			
UPS Case D x W x H (mm)	248 x 500 x 616		
WEIGHT			
Net Weight (kg)	30	38	38
INTERFACE			
Smart RS-232	Windows® 98/NT/2000/XP/2003/ME, Linux, Sun Solaris, IBM Aix, Compaq True64, SGI IRIX, FreeBSD, HP-UX, and MAC		
SNMP (Optional)	Power Management from SNMP Manager and Web Browser		



armenelectric
www.aec-ups.com

info@aec-ups.com
Phone: 88800888