



AEC1015 SERIES UPS 1500VA-10KVA

AEC1510 UPS Specification

Unit Individual Data							
Out Put Power (VA)	1500	2000	3000	5000	6000	8000	10000
Battery Voltage	24 V	36 V	36 V	48 V	60 V	60 V	96 V
First Start (VA)	1800	2400	3600	6000	7200	9500	12000
Dimension (Cm)	55*25*44		63*23*52		75*36*62		

Input Data
Voltage Range : 155 ~260 Volt AC
Frequency : 50 Hz ± 5%
Power Factor : ≥0.99
Total Harmonic Distortion : < 4%

Output Data
Voltage Range : 220 Volt AC
Frequency : 50 Hz
Power Factor : ≥0.8
Over Load : 120% rated Load for 30 sec
Over Load Cut : 150% rated load for 2 sec
Total Harmonic Distortion : ≤ 1%
Short Circuit : Ready

General Data
Topology : True Sine Wave
Control : Micro Controller
Charger : Full Automatic with Current and Voltage controller
Protections : Short Circuit Protection Surge – Sags- Spike – RFI – EMI – OL – B.W – B.C , Child Lock ON/OFF Key, Online Stabilizer

Monitoring and Control Data
Display Type : 2* 16 With Blue Backlight
Show on Screen : AC INPUT VOLTAGE , BATTERY VOLTAGE % , CHARGING % , LOAD % OVERLOAD, OUT PUT CUT OFF , BATTERY LOW , AC LINE HI , AC LINE DELAY , AC LINE LOW

ARMEN ELECTRIC CO.

1st Fl, No.138, Ostad Nejatollahi St. Corner of Sepand Cross Rd.
Tehran-Iran

Tel: 0098 21 88800888
Fax: 0098 21 88800888

<http://www.aec-ups.com>
E-mail: info@aec-ups.com

